

ROBUST 25 ProfiLINE



BASIC INFORMATION AND EQUIPMENT

- A robust construction
- Cast iron pump
- Maxispeed – automatic speed adjustment
- Extended cylinder stroke
- Splitting blade stroke adjustment
- Lifting bow for lifting heavier workpieces
- Lifting bow ratchet
- Left bow for securing the workpiece
- Movable lever for securing the workpiece during operation
- Control lever for two-handed activation
- High-quality hydraulic components
- Welded reservoir with an oil drain plug
- Submersible suction filter
- Oil level indicator

TEHNIČNI PODATKI

	R 25 K PL	R 25 E PL	R 25 EK PL
Pogon	kardan	elektromotor	kardan + elektromotor
Opis	LŽ črpalka	Hi-Lo 5,5 kW/400 V	LŽ črpalka Hi-Lo 5,5 kW/400 V
Vodenje sekire	maxispeed	maxispeed	maxispeed
Sila cepljenja (t)	25	25	25
Hod sekire (mm)	1100	1100	1100
Višina cepljenca	1150	1150	1150
Višina cepljenca na mizi (mm)	630	630	630
Premer cepljenca (mm)	900	900	900
Hitrost cepljenja H2/PH (cm/s)	28,5/30,6	17,9/15,0	glej levo
Potrebna moč traktorja (kW/KM)	30/41	/	30/41
Potreben navor kardana (Nm)	320	/	320
Kardan - največje število vrtljajev/min	540	/	540
Teža (kg)	505-625	565-655	575-665
Dimenzije V/Š/D/V1 (mm)	1800/856/1320/2710	1800/856/1320/2710	1800/856/1320/2710
Transportna višina z mizo (mm)	2050	2050	2050
Količina olja (l)	45	45	45
Tritočkovni traktorski priklop (kategorije)	I,II	I,II	I,II